

Randolph, NJ 07869

96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: info@govmark.com

Page 1

Received: 11/30	0/2010 Completed: 11/30/2010	Letter: L	rb	P.O.#:	Test Report #:	2-85546-0-RV	
Client's	Product Name: UltraCanvas Art	tist C325. 100%	Wove	n Polyester with Biodegradal	ole Water Base Coatii	ng Front and Back	
Identification	Side. End Use of Product: Digit	al Graphics.					
Tested For: Dwight Bessette				Key Test: NFPA 701-89 Sm NC RVNC			
U	Iltraflex Systems Inc.						
1	578 Sussex Tpk., Bldg. #4			Tel: 1-(97)	3)-664-6724 I	Ext:	

PC: 1H

Fax: 1-(973)-627-8506

TEST PERFORMED: NFPA 701 - Standard Methods of Fire Tests for Flame Resistant Textiles and Films 1989 Edition (Small Scale Procedure for Curtains & Draperies Weighing Less than 10 oz/yd²)

Note: NFPA 701 - 1989 Edition was specified by the older building codes for draperies, window treatments, and similar hanging decorations. The older building codes required both the Small Scale and Large Scale Tests.

In 1996 NFPA 701 was revised and an entirely different test was developed for draperies, window treatments, and similar hanging decorations. This single test (which replaces the 1989 Tests) is designated as Test Method 1.

RESULTS REPORTED: [x] Initially

[ ] After 3 dry cleanings

[ ] After 5 launderings @ 160°F

RESULTS:		Afterflame*	Flaming Drip	Char Length
	Specimen #	(seconds)	(seconds)	(inches)
Length:	1	0.0	1.0	4.0
1090	2	30.0+	3.0	5.9
	3	30.0+	2.6	4.2
	4	5.3	1.7	4.6
	5	4.7	2.3	4.1
Width:	6	13.2	0.6	5.6
	7	0.0	3.5	2.6
	8	10.1	2.2	4.8
	9	30.0+	0.0	5.4
	10	16.2	0.0	5.2
		P	vg: 1.7	Avg: 4.6

APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 9.7 oz/yd²

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

[x] Complies; [ ] Does not comply; [ ] Requires testing of 5 additional specimens



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 2 Received: 11/30/2010 | Completed: 11/30/2010 | Letter: L rb P.O.#: Test Report #: 2-85546-0-RV Client's Product Name: UltraCanvas Artist C325. 100% Woven Polyester with Biodegradable Water Base Coating Front and Back Identification Side. End Use of Product: Digital Graphics. Tested For: Dwight Bessette Key Test: NFPA 701-89 Sm NC RVNC Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Tel: 1-(973)-664-6724 Ext: Randolph, NJ 07869 Fax: 1-(973)-627-8506 ACCEPTANCE CRITERIA: Char Length (inches) Afterflame Flaming Drip (seconds) -----(seconds) Maximum Average Max.Avg. Max.Ind.Spec. \_\_\_\_\_ -----6.5" 2.0 7.5" \* Afterflame is required to be recorded; however, it is not factored into the Acceptance Criteria. RETEST PROVISION: Test 5 additional specimens if only 1 specimen exceeds 7.5" Char Length. REMARKS: None. CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 701 - 1989 Edition Small Scale Procedure for Curtains and Draperies. Robert I. Brown AUTHORIZED SIGNATURE THE GOVMARK ORGANIZATION, INC. / ec RV.12.10.10 (Page 2 of 2)